

## TECHNICAL CHARACTERISTICS - New 308

Summary - 03/2011

|   |   | PETROL   |   |                           |  |                                  |  |                           |   |                    |     |
|---|---|--|---|---------------------------|--|----------------------------------|--|---------------------------|---|--------------------|-----|
|   |   | 1.4 lVTi "98"<br>5-speed manual<br>EP3C Euro 5             | 1.6 lVTi "120"<br>5-speed manual<br>EP6C Euro 5                             |                           | 1.6 lVTi "120"<br>4-speed automatic              | 1.6 lTHP "156"<br>6-speed manual | 1.6 lTHP "156"<br>6-speed automatic<br>EP6CDT Euro 5 |                           | GTi 1.6 l - THP "200"<br>6-speed manual<br>EP6CDTX Euro 5 |                    |     |
| <b>GENERAL</b>                                    | Capacity (cm <sup>3</sup> )   | 1 397  |   | 1 598                     |  |                                  |  |                           |   |                    |     |
|   | Max. power in kW (or <b>bhp</b> ) / engine speed (rpm)              | 72 ( <b>98</b> ) / 6 000                                   |   | 88 ( <b>120</b> ) / 6 000 |  | 115 ( <b>156</b> ) / 6 000       |  | 147 (200) / 5 500 à 6 800 |   |                    |     |
|   | Max. torque (Nm)/engine speed (rpm)                                 | 136 / 4 000  |   | 160 / 4 250               |  | 240 / 1 400 à 4 000              |  | 275 / 1 700 à 4 500       |   |                    |     |
|   | Gearbox   | BE4 / 5N - 5-speed manual                                  | BE4 / 5N - 5-speed manual   | AT8 - 4-speed automatic   | MCM / B - 6-speed manual                         | AT6 - 6-speed automatic          | MCM / A - 6-speed manual                             |                           |   |                    |     |
| Tyres   | 195/65R15 <sup>(3)</sup> / 205/55R16 <sup>(3)</sup>                 |  | 195/65R15 <sup>(3)</sup> / 205/55R16 <sup>(3)</sup> / 225/45R17 / 225/40R18 |                           | 205/55R16 <sup>(3)</sup> / 225/45R17 / 225/40R18 |                                  | 225/40R18  |                           |   |                    |     |
| <b>PERFORMANCE</b><br>(driver only/<br>½ payload) | Maximum speed (kph)   | 182  |   | 195                       |  | 188                              |  | 214                       |   | 212                | 237 |
|   | Acceleration (seconds)  |  |   |                           |  |                                  |  |                           |   |                    |     |
|   | • 1000 m standing start   | <b>34,1</b> / 35,4   |   | <b>32,2</b> / 33,5        |  | <b>34,4</b> / 35,6               |  | <b>29,6</b> / 30,5        |   | <b>30,3</b> / 31,2 |     |
|   | • 0 to 100 kph  | <b>12,7</b> / 14,3   |   | <b>10,8</b> / 12,2        |  | <b>13,0</b> / 14,5               |  | <b>8,8</b> / 9,6          |   | <b>9,1</b> / 9,9   |     |
| In gear acceleration (seconds)                    |   |  |   |                           |  |                                  |  |                           |   |                    |     |
| • 80 to 120 kph in gear before top gear           | <b>12,4</b> / 14,1  |  | <b>10,9</b> / 12,4  |                           | <b>9,1</b> / 10,3 <sup>(2)</sup>                 |                                  | <b>8,9</b> / 10,1                                    |                           | <b>5,9</b> / 6,3 <sup>(2)</sup>                           |                    |     |
| • 80 to 120 kph in top gear                       | <b>18,6</b> / 21,3  |  | <b>15,8</b> / 18,1  |                           | --   |                                  | <b>11,5</b> / 13,1                                   |                           | --  |                    |     |
| <b>FUEL CONSUMPTION</b>                           | ECE - urban (litres/100 km)   | 8,4 <sup>(3)</sup>   |   | 9,1 <sup>(3)</sup>        |  | 9,3                              |  | 9,5 <sup>(3)</sup>        |   | 10,0               |     |
|   | EUDC - extra urban (litres/100 km)                                  | 5,1 <sup>(3)</sup>   |   | 4,9 <sup>(3)</sup>        |  | 5,1                              |  | 5,4 <sup>(3)</sup>        |   | 5,5                |     |
|   | Combined fuel consumption (litres/100 km)                           | 6,3 <sup>(3)</sup>   |   | 6,4 <sup>(3)</sup>        |  | 6,6                              |  | 6,9 <sup>(3)</sup>        |   | 7,2                |     |
|   | CO <sub>2</sub> emissions (g/km)                                    | 144 <sup>(3)</sup>   |   | 147 <sup>(3)</sup>        |  | 152                              |  | 159 <sup>(3)</sup>        |   | 166                |     |
|   | Fuel tank capacity (litres)   | 60   |   |                           |  |                                  |  |                           |   |                    |     |
| <b>DIMENSIONS (m)</b>                             | Overall length  | 4,276  |   |                           |  |                                  |  |                           |   |                    |     |
|   | Body width including door handles / with door mirrors folded / open | 1,815 / 1,879 / 2,038                                      |   |                           |  |                                  |  |                           |   |                    |     |
|   | Ride height (full tanks)  | 1,498  |   |                           |  |                                  |  |                           |   | 1,488              |     |
|   | Wheelbase   | 2,608  |   |                           |  |                                  |  |                           |   |                    |     |
|   | Front overhang / Rear overhang                                      | 0,926 / 0,742  |   |                           |  |                                  |  |                           |   |                    |     |
|   | Front track / Rear track  | 15": 1,536/1,531; 16"et 17": 1,526/1,521; 18": 1,522/1,517 |   |                           |  |                                  |  |                           |   |                    |     |
| <b>BOOT</b>                                       | Total boot volume (dm <sup>3</sup> ) <sup>(4)</sup>                 | 348 / 430  |   |                           |  |                                  |  |                           |   |                    |     |
| <b>WEIGHT (kg)</b>                                | Kerb weight (full tanks)  | 1 271  |   | 1 287                     |  | 1 312                            |  | 1 315                     |   | 1 368              |     |
|   |   |  |   |                           |  |                                  |  |                           |   |                    |     |
| <b>AERODYNAMICS</b>                               | SCx (m <sup>2</sup> )   | 0,68   |   |                           |  | 0,70                             |  |                           |   | 0,73               |     |

<sup>(1)</sup> With overboost    <sup>(2)</sup> Performance figures obtained in Automatic mode    <sup>(3)</sup> Energy saving tyres    <sup>(4)</sup> Boot volume shelf VDA standards in dm<sup>3</sup> / litres "of water"

## TECHNICAL CHARACTERISTICS - New 308

Summary - 03/2011

|   |   | DIESEL   |  |  |   |  |                            |     |                    |     |  |
|---|---|--|--|--|---|--|----------------------------|-----|--------------------|-----|--|
|   |   | 1.6 l HDi FAP "92"<br>5-speed manual<br>DV6D Euro 5        | 1.6 l e-HDi FAP "112"<br>6-speed manual  | 1.6 l e-HDi FAP "112"<br>6-speed electronically<br>controlled<br>DV6C Euro 5 | 2.0 l HDi FAP "150"<br>6-speed manual<br>DW10D Euro 5             | 2.0 l HDi FAP "163"<br>6-speed automatic<br>DW10C Euro 5 |                            |     |                    |     |  |
| <b>GENERAL</b>                                    | Capacity (cm <sup>3</sup> )   | 1 560  |  |  |   | 1 997  |                            |     |                    |     |  |
|   | Max. power in kW (or <b>bhp</b> ) / engine speed (rpm)              | 68 ( <b>92</b> ) / 4 000                                   | 82 ( <b>112</b> ) / 3 600  |  |   | 110 ( <b>150</b> ) / 3 750                               | 120 ( <b>163</b> ) / 3 750 |     |                    |     |  |
|   | Max. torque (Nm)/engine speed (rpm)                                 | 230 / 1 750  | 270 - 285 <sup>(1)</sup> / 1 750 - 2 000                                       |  |   | 340 / 2 000 - 3 000                                      |                            |     |                    |     |  |
|   | Gearbox   | BE4 / 5L - 5-speed manual                                  | MCM / E - 6-speed manual   | MCP / D - 6-speed electronically controlled                                  |   | ML6L - 6-speed manual                                    | AM6C - 6-speed automatic   |     |                    |     |  |
|   | Tyres   | 195/65R15 <sup>(3)</sup> / 205/55R16 <sup>(3)</sup>        | 195/65R15 <sup>(3)</sup> / 205/55R16 <sup>(3)(6)</sup> / 225/45R17 / 225/40R18 | 205/55R16 <sup>(3)</sup> / 225/45R17 / 225/40R18                             |   |  |                            |     |                    |     |  |
| <b>PERFORMANCE</b><br>(driver only/<br>½ payload) | Maximum speed (kph)   | 181  | 190  |  |   | 205  | 202                        |     |                    |     |  |
|   | Acceleration (seconds)  |  |  |  |   |  |                            |     |                    |     |  |
|   | • 1000 m standing start   | <b>34,0</b> / 35,2   | <b>32,8</b> / 33,9   | <b>32,7</b> / 33,9   |   | <b>30,1</b> / 30,9                                       | <b>30,9</b> / 31,8         |     |                    |     |  |
|   | • 0 to 100 kph  | <b>12,4</b> / 14,0   | <b>11,4</b> / 12,5   | <b>11,4</b> / 12,5   |   | <b>8,8</b> / 9,5   | <b>9,6</b> / 10,4          |     |                    |     |  |
|   | In gear acceleration (seconds)                                      |  |  |  |   |  |                            |     |                    |     |  |
| • 80 to 120 kph in gear before top gear           | <b>10,5</b> / 11,8  | <b>10,9</b> / 12,3   | <b>8,2</b> / 9,2 <sup>(2)</sup>  |  | <b>7,8</b> / 8,7  | <b>6,3</b> / 6,9 <sup>(2)</sup>                          |                            |     |                    |     |  |
| • 80 to 120 kph in top gear                       | <b>13,2</b> / 14,8  | <b>14,5</b> / 16,5   | -  |  | <b>10,2</b> / 11,4  | -  |                            |     |                    |     |  |
| <b>FUEL CONSUMPTION</b>                           | ECE - urban (litres/100 km)   | 5,2 <sup>(3)</sup>   | 5,2 <sup>(6)</sup> / 5,3 <sup>(3)</sup>  | 5,4  | 4,4 <sup>(6)</sup> / 4,8 <sup>(3)</sup>                           | 4,9  | 6,1 <sup>(3)</sup>         | 6,5 | 8,1 <sup>(3)</sup> | 8,3 |  |
|   | EUDC - extra urban (litres/100 km)                                  | 3,6 <sup>(3)</sup>   | 3,6 <sup>(6)</sup> / 3,9 <sup>(3)</sup>  | 4,0  | 3,7 <sup>(6)</sup> / 3,8 <sup>(3)</sup>                           | 4,0  | 4,2 <sup>(3)</sup>         | 4,3 | 5,0 <sup>(3)</sup> | 5,2 |  |
|   | Combined fuel consumption (litres/100 km)                           | 4,2 <sup>(3)</sup>   | 4,2 <sup>(6)</sup> / 4,4 <sup>(3)</sup>  | 4,5  | 4,0 <sup>(6)</sup> / 4,2 <sup>(3)</sup>                           | 4,3  | 4,9 <sup>(3)</sup>         | 5,1 | 6,1 <sup>(3)</sup> | 6,3 |  |
|   | CO <sub>2</sub> emissions (g/km)                                    | <b>110<sup>(3)</sup></b>                                   | <b>109<sup>(6)</sup></b> / 115 <sup>(3)</sup>                                  | 118  | <b>98<sup>(6)</sup></b> / 104 <sup>(6)</sup> / 109 <sup>(3)</sup> | 114  | 129 <sup>(3)</sup>         | 134 | 159 <sup>(3)</sup> | 164 |  |
|   | Fuel tank capacity (litres)   | 60   |  |  |   |  |                            |     |                    |     |  |
| <b>DIMENSIONS (m)</b>                             | Overall length  | 4,276  |  |  |   |  |                            |     |                    |     |  |
|   | Body width including door handles / with door mirrors folded / open | 1,815 / 1,879 / 2,038                                      |  |  |   |  |                            |     |                    |     |  |
|   | Ride height (full tanks)  | 1,498  |  |  |   |  |                            |     |                    |     |  |
|   | Wheelbase   | 2,608  |  |  |   |  |                            |     |                    |     |  |
|   | Front overhang / Rear overhang                                      | 0,926 / 0,742  |  |  |   |  |                            |     |                    |     |  |
|   | Front track / Rear track  | 15": 1,536/1,531; 16"et 17": 1,526/1,521; 18": 1,522/1,517 |  |  |   |  |                            |     |                    |     |  |
| <b>BOOT</b>                                       | Total boot volume (dm <sup>3</sup> ) <sup>(4)</sup>                 | 348 / 430  |  |  |   |  |                            |     |                    |     |  |
| <b>WEIGHT (kg)</b>                                | Kerb weight (full tanks)  | 1 200  | 1 318  | 1 320  | 1 398   | 1 428  |                            |     |                    |     |  |
| <b>AERODYNAMICS</b>                               | SCx (m <sup>2</sup> )   | 0,67   | 0,64 <sup>(6)</sup> / 0,68   | 0,64 <sup>(6)</sup> / 0,67   | 0,69  |  |                            |     |                    |     |  |

<sup>(1)</sup> With overboost <sup>(2)</sup> Performance figures obtained in Automatic mode <sup>(3)</sup> Energy saving tyres <sup>(4)</sup> Boot volume shelf VDA standards in dm<sup>3</sup> / litres "of water"

<sup>(5)</sup> Available in 98 g/km CO<sub>2</sub> to the summer 2011 <sup>(6)</sup> With tyres with Very Low Rolling Resistance